

AVR-4310CI

AV Surround Receiver

DENON



A/V Surround Receiver featuring Advanced Connectivity, Network Audio and Photo Streaming and an interface that enhances your level of entertainment enjoyment

The AVR-4310CI is a 7-channel A/V surround receiver that not only offers DENON LINK 4th and high-bit i/p conversion and scaling along with other acclaimed Denon audio and video technologies, but also lets users enjoy a wide variety of media such as Network Audio and Photo Streaming.



Features

New features

- HDMI Clock Control via DENON LINK 4th
- Clock Jitter Reducer available for all digital inputs
- Audyssey DSX processing
- Dolby Pro Logic IIz processing
- High bit i/p converter and scaler up to 1080p featuring Anchor Bay VRS processing
 - Multi cadence detection for SD and HD video signal
 - Digital noise reduction and enhancer
- 6 x HDMI in (1 x front panel)
- 2 x HDMI out (Repeater and Scaler)
- USB digital direct connection for iPod® (audio only)
- Enhance network capability
 - Napster and Rhapsody online subscription based service support

State-of-the-art Denon Solutions for Maximizing Content Quality

- Identical quality and power for all 7 channels, 130W x 7ch
- Dynamic Discrete Surround Circuit, D.D.S.C.-HD
 - New dual 32-bit floating point high precision DSP processors
 - AL24 Plus processing, to dramatically enhance the music listening experience
 - Differential D/A Converters
- Stable power supply for high-quality sound and picture playback
- Compressed Audio Restorer to enhance digital music files
- Dolby TrueHD and DTS-HD Master Audio decoders
- Denon's high picture quality circuitry, to enhance enjoyment of existing DVDs
- Video digital noise reduction, to optimize effects for both SD and HD content
- Vertical Stretch (supporting the CinemaScope aspect ratio)

Connectivity & Future-ready Expandability

- Internet Radio and Network audio/photo streaming from PC/MAC, server
- Mass storage support USB for audio and photo playback (MTP compatible)
- XM and Sirius satellite radio ready
- 3 source / 3 zone capability
- Power amplifier assign for zone 2 or 3

Ease-of-use

- Advanced GUI, Superimposed on HDMI (up to 1080p)
- Dual HDMI outputs enabling simultaneous output to video projector and flat panel
- Audyssey Dynamic Volume, for real-time volume adjustment
- Audyssey Dynamic EQ selects the correct frequency response and surround volume levels on a moment by moment basis
- Audyssey MultEQ XT Auto setup and Room EQ room acoustic correction system
- 2-line fluorescent display on front panel
- Sleep timer function
- Three Quick Select Buttons
- EL pre memory & learning remote control unit +zone remote control unit

Custom Integration

- Audyssey Pro Installer Program compatible
- Remote Installer Access via DPMS
- PC setup via Ethernet (Web setup)

State-of-the-art Denon Solutions for Maximizing Content Quality

• HDMI Clock Control via DENON LINK 4th

DENON LINK is proprietary high-quality digital audio transmission technology that utilizes a real-time balanced transmission system to protect the signal from external noise. With the more advanced Denon Link 4th used in an HDMI connection, for HD audio read from Blu-ray disc as well, the master clock that operates the D/A converter of the A/V surround receiver is transmitted to the player, enabling the circuitry to be operated while sharing the same clock in order to achieve digital audio transmission with negligible jitter. Sound localization becomes more precise, and a greater sense of space is produced in the sound images. When combined with a Denon Blu-ray player that supports Denon Link 4th, users will be able to enjoy the highest level of sonic quality that is expected from HD audio.

• Clock Jitter Reducer available for all digital inputs

The Clock Jitter Reducer thoroughly suppresses fluctuations on the clock waveform to remove distortion from the digital audio signal and minimize adverse influences on sound quality.

• Support for new surround extension

By assigning 7 channels of power from the AVR-4310CI's built-in power amp to individual channels, you can create and enjoy your own custom surround mode.

-Audyssey DSX processing

Audyssey DSX extends 5.1-channel and 7.1-channel sound sources to a wider and higher dimension. A sound that is wider to the left and right is achieved by adding a sound source (LW/ RW) that is wider than the usual placement of the front (FL/ FR) speakers, and a greater sense of height in sound space is achieved by adding a sound source (LH/RH) in the upper area between the FL(FR) and LW(RW) channels.

-Dolby Pro Logic IIz processing

Dolby Pro Logic IIz is surround technology that adds front height channel sound sources above the front left and right speakers to enable 7.1-channel playback for 5.1-channel program sources or 9.1-channel playback for 7.1-channel sources such as Blu-ray. Since the dimension of height is being added to the conventional surround sound, you can experience sound movements above you while watching movies or playing games. With music, the sound space of a concert hall is more realistically reproduced.

• Minimum Signal Path for clear audio and video signal

• Direct Mechanical Ground Construction, embodying concepts for thorough vibration resistance

• Digital / analog separate windings

• Compressed Audio Restorer to enhance digital music files

Connectivity & Future-ready Expandability

• 6 x HDMI in (1 x front panel)

An HDMI input has been provided on the front panel for quick, easy connection of an external devices such as a video camera or game console.

• USB digital direct connection for iPod (audio only)

The AVR-4310CI has USB ports for digital audio input from an iPod to let you enjoy music in high-quality sound made possible by acclaimed Denon audio technologies such as DDSC-HD and the combination of AL24 Processing and high-performance D/A converters. You can also operate the system while viewing information from the iPod, including music information, on the TV screen through the AVR-4310CI's GUI function. Simply use the USB cable that came with your iPod to connect it to the AVR-4310CI.



• Audio/video playback and control for iPod with optional dock (ASD-11R)

• Includes dedicated zone remote control unit

• 2way remote ready (optional: Denon RC-7000CI/RC-7001RCI)

Ease-of-use

• Advanced GUI, Superimposed on HDMI (up to 1080p)

The AVR-4310CI is equipped with an easy-to-view Graphical User Interface (GUI) featuring visual menu displays and hierarchical directories. The hierarchical directory displays let you easily see where you are and what settings you want to make. Operation has been simplified as well. These menu displays can also be output to the monitor over HDMI.

• Auto surround mode

• Audio level memory, capable of correcting different signal levels for each input device

• Variable subwoofer crossover switching

Custom Integration

• AMX, Crestron third party IP control support with RS-232C port

• 150mA Trigger output

• IR Remote in/out ports

Ports

In		
HDMI		x 6
Component		x 3
S-Video		x 7
Composite (Video)		x 7
Analog Audio (Tuner included)		x 10
Analog EXT. Input		7.1ch
DENON LINK 4th		x 1
Digital Optical		x 3
Digital Coaxial		x 3
Out		
HDMI Monitor		x 2
Component Monitor		x 1
S-Video Monitor		x 1
S-Video		x 2
Composite Monitor		x 1
Composite (Zone2)		x 1
Analog Audio REC		x 2
Audio Preout (Zone2 / Zone3 / 7.1ch)		x 3
Digital Optical		x 1
Phones		x 1
Other		
Microphone Port		x 1
Dock Control Port		x 1
FM Tuner Antenna		x 1
AM Tuner Antenna		x 1
Sirius Connector		x 1
XM connector		x 1
Ethernet		x 1
USB (selectable front or back panel)		x 2
RS-232C		x 1
Remote Control In/Out		In 1 / Out 1
DC12V 150mA MAX. trigger out		x 2

Main Specifications

Power amplifier section		Preamplifier section	
Rated output	*THD figures are power amp stage values.	Input sensitivity/impedance	
Front L/R	130 W + 130 W (8 ohms, 20 Hz - 20 kHz, THD 0.05 %) 170 W + 170 W (6 ohms, 1 kHz, THD 0.7%)	PHONO (MM)	2.5 mV
Center	130 W (8 ohms, 20 Hz - 20 kHz, THD 0.05 %) 170 W (6 ohms, 1 kHz, THD 0.7%)	Audio inputs	200 mV/47 kohms
Surround L/R	130 W + 130 W (8 ohms, 20 Hz - 20 kHz, THD 0.05 %) 170 W + 170 W (6 ohms, 1 kHz, THD 0.7%)	Output level/Load impedance	
Surround Back L/R	130 W + 130 W (8 ohms, 20 Hz - 20 kHz, THD 0.05 %) 170 W + 170 W (6 ohms, 1 kHz, THD 0.7%)	Audio outputs	1.2 V
		FM section	
		Tuning frequency range	87.5 - 107.9 MHz
		Usable sensitivity	1.5 µV (14.8 dBf)
		AM section	
		Tuning frequency range	530 - 1710 kHz
		Usable sensitivity	20 µV
		General	
		Power supply	AC 120 V, 60 Hz
		Power consumption	8.1 A (Standby 0.1 W)
		Dimensions (W x H x D)	17-3/32" x 6-47/64" x 16-19/64"
			434 x 171 x 414 mm
		Weight	34 lbs 13 oz, 15.8 kg



*Design and specifications are subject to change without notice.
 **Dolby®, Pro Logic® and the double-D symbol are trademarks of Dolby Laboratories.
 *DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademarks of DTS, Inc.
 *HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
 *Neural® and Neural Audio® and Neural Surround® are trademarks of Neural Audio Corporation.
 *NSV is a registered trademark of Analog Devices, Inc.
 *Audyssey MultEQ® is a registered trademark of Audyssey Laboratories.
 Audyssey Dynamic EQ™ is a trademark of Audyssey Laboratories.
 Audyssey Dynamic Volume™ is a trademark of Audyssey Laboratories.
 *Microsoft, Windows Media, Windows Vista, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
 *HD Radio™ Technology Manufactured Under License From iBiquity Digital Corporation. iBiquity Digital, the HD Radio logo, and the HD logo are registered trademarks of iBiquity Digital Corporation. HD Radio™ is a trademark of iBiquity Digital Corporation. U.S. and Foreign Patents.
 *The XM name and related logo are registered trademarks of XM Satellite Radio reserved.
 *XM Ready™ is a registered trademark of XM Satellite Radio Inc.
 *iPod® is a trademark of Apple Inc., registered in the U.S. and other countries.